

ACF-2064-DW

SPECIALTY DOORS

Steel Flush Acoustical Access Door with Drywall Bead Flange

Highest STC & OITC Rating in the INDUSTRY

Application

- This flush access door is ideal for use on Acoustical walls and ceilings where maintaining STC Rating (Sound Transmission Class) and OITC Rating (Outdoor-Indoor Transmission Class) is required

Product Features

- Zinc coated steel provides superior corrosion resistance
- Drywall taping bead flange
- Type 304 Stainless steel with #4 satin polish also available
- Tested and evaluated to ASTM: E90(09), ASTM: E413(16), ASTM: E1332(16) and certified to STC Rating 64 and OITC Rating 54

ACF-2064-DW Door Specifications:

Material: 18 Gauge Satin Coat Steel

Door: 18 Gauge, encapsulated design with 2" thick acoustical mineral liner and 0.11" thick mineral filled vinyl barrier

Frame: 18 Gauge, press bent for strength and rigidity, drywall taping bead flange Insulated with 1" thick acoustical mineral liner

Gasket: 1/8" x 1/2" Neoprene Rubber with Adhesive.

Hinge: Continuous exposed stainless steel piano hinge

Standard Lock: Slotted Screwdriver Cam Latch

Optional Lock: Torx head with security pin

Acoustic Rating: This door has been tested and evaluated to ASTM: E90(09), ASTM: E413(16), ASTM: E1332(16) and certified to STC Rating 64 and OITC Rating 54.

Finish: Baked White Prime Coat

(Additional finish paint is recommended for superior corrosion resistance)

ACF-2064-DW STANDARD SIZES

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
12 x 12	305 x 305	1	14.0	6.4
16 x 16	406 x 406	1	26.0	11.8
18 x 18	457 x 457	1	35.0	15.9
24 x 24	610 x 610	1	42.0	19.1
24 x 36	610 x 914	2	62.0	28.1

