

# ARCH-STICK

## OUTSIDE 90° ARCHED CORNER BEAD

Produces Perfect Outside  
90° Arched Corners  
Eliminating Flat Spots.

### APPLICATIONS

- Arched windows and doors.
- Curved walls, ceilings, soffits, and staircases.
- Free-form, custom drywall applications where a seamless installation is required.

### PRODUCT DESCRIPTION


- Clean installation. No mess.
- Tempered steel backbone for perfect arches.
- Patented tear strips allow for easy straight-to-curve transitions.
- PUR-laminated nose resists dents and provides a beautiful corner without fuzz-up during finishing and sanding.
- Second coat of compound can be applied immediately – very light skim coat to finish.
- Easily installs using standard compounds. No special tools or fasteners needed. No nail pops.
- Available in 305 cm (10ft) lengths.
- Waterproof. Rustproof.



PROFESSIONAL GRADE

## ADVANTAGES OVER COMPETITORS

ARCH-STICK	COMPETITOR ARCHED CORNER BEAD
Tempered-steel backbone for perfect arches. No flat spots.	Tends to kink when applying to arches
Patented tear strips eliminate transporation damage to tabs	Tabs can be damaged during transport
Double-sided tabs allow for product to curve on both sides	Only has tabs on one side of product
Composite material creates Superior bonding	PVC material does not bond with compounds or paint Adequate bonding



## DIRECTIONS FOR USE

- 1 Fold over and remove tear strip from both sides of ARCH-STICK. Using ARCH-STICK as a ruler, cut to length. For a perfect straight-to-curve transition, leave tear strip intact in straight areas.
- 2 With a 4" or 5" taping knife, apply a smooth, liberal coat of compound to corner. Press ARCH-STICK firmly into compound to form a uniform curve. Wipe down tight and smooth with a 4" or 5" taping knife. Let dry for several hours or overnight. *Where material meets or for irregular framing, use thumb tacks, small nails, or paper tape to hold ARCH-STICK in place to ensure a smooth arch.*
- 3 Use a taping knife or sanding block to remove any high spots to create a flat, level surface. Apply a fill coat of compound feathering the compound beyond the previous coat. (Fill coat can be applied immediately after STEP TWO, if desired.) Lightweight compound used in this step makes sanding much easier. Let dry for several hours or overnight.
- 4 Apply finish coat. Let dry for several hours or overnight. When transitions occur between curved and straight areas, ARCH-STICK's profile matches most conventional corner beads.
- 5 Sand lightly with 150 grit sandpaper. ARCH-STICK will not fuzz-up like other paper-faced arched products.

## SPECIFICATIONS

- 86 mm x 305 cm stick (3 3/8" x 10')
- Color Code BLACK
- Item#: AS10-285735  
UPC: 656690212386  
Case Pack: 25pc.  
24 cases per pallet  
Pallet weight: 336kg (741lb)

## STORAGE

Store in a dry place protected from moisture.



Manufactured by Strait-Flex for CGC Inc.  
350 Burnhamthorpe Rd. W, 5th Floor,  
Mississauga, ON L5B 3J1

For product information call 1-800-387-2690 or go to [cgcinc.com](http://cgcinc.com)

MK\_IFP021\_E/03-13