

# AS-9000-DW

## SPECIALTY DOORS

### Gasketed Drywall Access Door

#### Application

- Designed to provide a gasketed fit in drywall walls and ceilings
- This door is commonly used in clean rooms, laboratories, operating rooms, etc.

#### Product Features

- Gasketed access door
- Formed door panel with reinforced edges and a concealed hinge, along with open cell gasket between the door and frame
- Drywall taping bead flange.

#### AS-9000-DW Access Door Specifications:

**Door / Door Frame:** Stainless Steel or Carbon Steel: 18 gauge door, 18 gauge mounting frame, flange to be drywall taping bead flange.

**Hinge:** Concealed

**Gasket:** Pemko S88 adhesive-backed bulb silicone gasket

**Standard Latch:** Stainless Steel Slotted Screwdriver Cam Latch

**Optional Latches/Locks:** Cylinder lock & key, allen head cam latch, spanner head cam latch, torx head with security pin

**Finish:** Baked White Prime Coat

(Additional finish paint is recommended for superior corrosion resistance)

*Please note the AS-9000 has not been tested for air penetration.*

*For a door that has been tested for Air & Water penetration see ADWT model.*

#### AS-9000-DW STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Weight per Door	
Inches	mm	lbs.	kg.
8 x 8	203 x 203	4.0	1.8
12 x 12	305 x 305	5.0	2.3
16 x 16	406 x 406	7.5	3.4
18 x 18	457 x 457	8.8	4.0
24 x 24	610 x 610	13.9	6.3
24 x 36	610 x 914	20.5	9.3

Wall or ceiling opening is nominal door size + 3/8" (9 mm)

For detailed specifications see submittal sheet

