

CIRRUS® Second Look®

Scored Tegular
medium texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Cirrus Second Look III panels with Suprafine XL 9/16" suspension system

See more photos at:
armstrongceilings.com/photogallery

Medium texture panels with a scored plank visual; offer both Sustain® and Total Acoustics® panel performance.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Cirrus® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Classic Cirrus texture
- Excellent score line painting for a clean visual
- Mold- and mildew-resistant surface
- USDA-certified Biobased Product – 91%
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White
(WH)



Custom Colors
Available

FACE VIEW



Cirrus® Second Look® I panel –
Scoring creates nominal 12" x 12" squares



Cirrus® Second Look® II panel –
Scoring creates nominal 24" x 24" squares



Cirrus® Second Look® III panel –
Scoring creates nominal 6" x 48" linear planks

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Cirrus Second Look III
2. Cirrus Second Look III with Suprafine® 9/16" suspension system

CIRRUS® Second Look®

Scored Tegular
medium texture



RECYCLED
CONTENT
UP TO
77%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
CIRRUS® Second Look® I 15/16" Beveled Tegular	14	512	24 × 48 × 3/4"	
CIRRUS® Second Look® II 9/16" Beveled Tegular	28	510	24 × 48 × 3/4"	
15/16" Beveled Tegular	14	513	24 × 48 × 3/4"	
CIRRUS® Second Look® III 9/16" Beveled Tegular	28	511	24 × 48 × 3/4"	
15/16" Beveled Tegular	14	514	24 × 48 × 3/4"	

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
NRC + CAC =	NRC CAC									
0.65 35	GOOD	Class A	0.85	*	Std	*	Std	*	*	10-Yr
0.65 35	GOOD	Class A	0.85	*	Std	*	Std	*	*	10-Yr
0.65 35	GOOD	Class A	0.85	*	Std	*	Std	*	*	10-Yr
0.65 35	GOOD	Class A	0.85	*	Std	*	Std	*	*	10-Yr
0.65 35	GOOD	Class A	0.85	*	Std	*	Std	*	*	10-Yr

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS

NOTE: It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.



PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification

Type A, Form A1.2, Pattern F, I; Fire Class A

Humidity/Sag Resistance

Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor – 1.9 (BTU units)

R Factor – 0.33 (Watts units)

Design Consideration

Do not mix Cirrus Second Look with standard Cirrus items in the same room. It is not recommended to install Silhouette or Interlude grid with Second Look panels.

Warranty

Details at armstrongceilings.com/warranty

Weight: Square Feet/Carton

1.09 LBS/SF; 48 SF/CTN

Minimum Order Quantity

1 carton

Metric Items Available

512M, 510M, 513M, 511M, 514M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.