

## Deflection Bead Submittal Sheet

STOCK NO.	LENGTH	PCS. PER BOX
9220	10'	48



**Description:** Trim-Tex Deflection Bead is designed to prevent inside corner cracking when installed against a ceiling or concrete deck that may be subject to up to  $\frac{7}{16}$ " movement.

**Advantages:** Made from rust proof, dent resistant PVC to reduce jobsite and handling damage. Does not contain cellulose, a potential food source for mold.

**Limitations:** Product is designed for interior use.

**Applicable Standards:** Rigid PVC products made by Trim-Tex meet ASTM specifications D3678, D1784, C1047 and achieve a Class A rating for flame spread and smoke developed when tested under ASTM E84. Can be used in fire-rated and non fire-rated assemblies. UL Classified when installed with CEMCO® FAS® Track 1000. Deflection Bead is UL classified for fire rated joint-systems, see UL fire resistance directory R38710. STC 53 rating with two layers of  $\frac{5}{8}$ " type gypsum on both sides of wall. STC 50 rating with two layers of  $\frac{5}{8}$ " type gypsum on one side of wall and one layer  $\frac{5}{8}$ " type gypsum on other.

**Surface Characteristics:** Trim-Tex products are made from PVC. PVC does not support combustion and is self-extinguishing when the source of flame or heat is removed.

**Installation:** Trim-Tex recommends following established acceptable industry standard installation methods. Detailed installation instructions can be found at [www.trim-tex.com](http://www.trim-tex.com).


**Finishing:** Always use a high quality paint.

**Accessories:** 847 Spray Adhesive and Safety Products distributed by Trim-Tex.

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_

Date \_\_\_\_\_



Approvals (Signatures or Stamps)