

DW-5058R

Recessed Access Door, Drywall (Round) Panel Door

Application

• Designed to provide access in walls and ceilings, while maintaining an invisible, architecturally pleasing appearance

Product Features

• Designed to accommodate 5/8" drywall.

Standard with a touch latch feature



Material: aluminum extrusion with 5/8" drywall in door panel

Door: .080" aluminum extrusion

Door Frame: .080" aluminum extrusion recessed to provide similar edge to drywall bead to allow for finishing of wall or ceiling surface.

Hinge: Hinge allows door panel to open to 90 degrees, and also allows for door panel to be removed from frame. Safety chain installed on door & frame for safety.

Standard Latch: Concealed Touch Latches

Optional Latches/Locks: Slotted Screwdriver Cam Latch, allen head cam latch, spanner head cam latch, cylinder lock & key.

Finish: Mill Finish. Drywall is ready to be finished to match surrounding wall or ceiling surface.

STANDARD SIZES (other sizes available upon request)

Door Dia.		Weight per Door	
inches	mm	lbs.	kg.
12	305	2.0	0.9
16	406	5.0	2.3
18	457	6.0	2.7
24	610	12.0	5.5

Wall opening is normal door size plus +3/8" (9.5mm) For detailed specifications see submittal sheet



