

# ED-2002

## UNIVERSAL FLUSH

### Application

- Installation in Drywall, Plaster, Masonry, Tile or any flush surface
- Economical and attractive access door for walls & ceilings

### Product Features

- Formed door panel
- Concealed hinge

### ED-2002 Access Door Specifications:

**Material:** 18 gauge steel door and frame

**Door:** Flush to frame with reinforced edges

**Door Frame:** 1" wide outside flange with 1 7/16" deep mounting Frame: Knock over mounting tabs provided on 6x6, 8x8, 10x10 and 12x12

**Hinge:** Concealed Hinge Pin

**Latch:** Stainless Steel Slotted Screwdriver Cam Latch

**Finish:** Baked White Prime Coat

(Additional finish paint is recommended for superior corrosion resistance)

### ED-2002 STANDARD SIZES

| Nominal Door Size W&H |           | Latches | Weight per Door |      |
|-----------------------|-----------|---------|-----------------|------|
| Inches                | mm        |         | lbs.            | kg.  |
| 6 X 6                 | 152 X 152 | 1       | 1.5             | 0.7  |
| 8 X 8                 | 203 X 203 | 1       | 2.1             | 1.0  |
| 10 X 10               | 254 X 254 | 1       | 2.9             | 1.3  |
| 12 X 12               | 305 X 305 | 1       | 3.7             | 1.7  |
| 14 X 14               | 356 X 356 | 1       | 4.6             | 2.1  |
| 16 X 16               | 406 X 406 | 1       | 5.6             | 2.5  |
| 18 x 18               | 457 x 457 | 1       | 6.8             | 3.1  |
| 20 x 20               | 508 x 508 | 1       | 8.2             | 3.7  |
| 24 x 24               | 610 x 610 | 1       | 10.3            | 4.7  |
| 24 x 36               | 610 x 914 | 2       | 16.9            | 7.7  |
| 30 x 30               | 726 x 762 | 2       | 21.2            | 9.6  |
| 36 x 36               | 914 x 914 | 2       | 24.5            | 11.1 |

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

