

FW-5015

Fire Rated Access Door, *Recessed for Drywall walls*

Application

- For installation in drywall walls requiring concealing of the door panel consistent to surroundings
- For use in walls, fire-rated for up to 90-minutes with a temperature rise of max 250°C (450°F) over 30 minutes

Product Features

- Recessed reinforced door fitted with 5/8" Fire-rated drywall.
- Concealed hinge & self-centering device ensures seamless appearance in walls
- Self-closing & self-latching door mechanism
- Perforated Frame ensures trouble-free application of skim coat to edge of the door
- Zinc coated steel provides superior corrosion resistance
- Testing standards UL 10B; CAN/ULC S104

FW-5015 Access Door Specifications:

Door: Steel-22 Gauge recessed fitted with 5/8" thick drywall suitable to accept skim coat finish on site.

Door Frame: Steel-22 Gauge press bent for strength and rigidity with pre-punched flanges for convenient mounting and accepting skim coat finish on site

Hinge: Concealed

Fire Rating (Walls): Meets 1½ hour fire rating requirement in accordance with UL 10B; CAN/ULC S104 for max size upto 24" x 36"

Latch: Self-latching bolt, operated by flush key

Finish: Satin coat steel

FW-5015 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
12 X 12	305 X 305	1	8	3.6
16 X 16	406 X 406	1	13	5.9
18 X 18	457 X 457	1	16	7.3
24 X 24	610 X 610	1	25	11.3
24 X 36	610 X 914	2	40	18.1

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

PATENT PENDING



PATENT PENDING

