

# FW-5050-UP

## Fire Rated Insulated Upswing Door for Ceilings

### Application

- An insulated, fire rated access door for inward opening in ceilings

### Product Features

- For fire rated ceilings, this door has been approved by Warnock Hersey International for 3 hours (max. size to 24"x 36")
- Insulated Door Panel
- Inside Latch Release

### FW-5050-UP Access Door Specifications:

**Material:** Steel or Stainless Steel

**Door:** 16 gauge, Flush to frame with reinforced edges filled with 2" thick fire insulation

**Mounting Frame:** 16 gauge mounting frame, with trim 1" wide

**Hinge:** Concealed with coil spring for dampening

**Fire Rating:** For Ceilings: Warnock Hersey International 3 hour rated in a non-combustible ceiling. 1 hour rated in a combustible ceiling.  
Max size: 24x 36

**Standard Compliances:** ASTM E119; CA/ULC-S101; NFPA 251; UBC 43-7

**Standard Latch:** L Handle - operable from both sides

**Finish:** Baked White Prime Coat

(Additional finish paint is recommended for superior corrosion resistance)

### FW-5050-UP STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
22 X 36	559 X 914	2	38	17.2
22 X 30	559 X 762	2	44	20.0
24 X 24	610 X 610	1	46	20.9
24 X 36	610 X 914	2	49	22.2

Wall or ceiling opening is W + 1/2" ( 12 mm)

For detailed specifications see submittal sheet

