

# USG PREMIER NUBBY™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE



USG Premier Nubby™ Acoustical Panels with ClimaPlus™ Performance/  
USG Donn® Brand Centricite™ DXT™ Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



## FEATURES AND BENEFITS

- High-quality nubby cloth facing offers consistent, fine-textured appearance.
- Excellent noise reduction with NRC of 0.85 or 0.90 meets the demanding sound-control needs of open-plan spaces.
- Lightweight fiberglass basemat makes installation fast and easy.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

## APPLICATIONS

- Conference rooms and executive areas
- Gymnasiums and auditoriums
- Open-office plans
- Retail stores

## SUBSTRATE

- Fiberglass

Lightly Textured Panel



# USG PREMIER NUBBY™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

30

YEAR LIMITED SYSTEM  
WARRANTY  
• No Visible Sag  
• Mold/Mildew Protection

FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
usgdesignstudio.com  
cgcdesignstudio.com

ORDER SAMPLES/LITERATURE  
USG: samplit@usg.com  
fax: 888 874-2348 | usg.com  
CGC: contact Sales Representative  
TECHNICAL SERVICES  
800 USG.4YOU (874-4968)

## USG PREMIER NUBBY™ PANELS

Edge	Panel Size	Fire Rating	Item No.	UL Classified		LR <sup>2</sup>	Color	Grid Options	Anti-Mold & Mildew	Recycled Content <sup>1</sup>	Panel Cost
				NRC	CAC						
SQ	2'x2'x3/4"	Class A	7000G	0.85	—	0.87	White	A,B,C		30%	\$\$\$
	2'x2'x1"	Class A	7002G	0.90	—	0.87	White	A,B,C		33%	\$\$\$
	2'x2'x1" Foil-Back	Class A	7012G	0.90	25	0.87	White	A,B,C		33%	\$\$\$
	2'x4'x1"	Class A	7003G	0.90	—	0.87	White	A,B		33%	\$\$\$
	2'x4'x1" Foil-Back	Class A	7013G	0.90	25	0.87	White	A,B		33%	\$\$\$

### ClimaPlus™ Warranty Performance<sup>3</sup>

Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

## GRID PROFILE OPTIONS

A USG DX™/DXL™	B USG DXW™	C <sup>4</sup> USG Centricitee™ DXT™

## PHYSICAL DATA/ FOOTNOTES

<b>Product literature</b> Data sheet: SC1839	<b>Online tools</b> usgdesignstudio.com or cgcdesignstudio.com	<b>Maintenance</b> Can be cleaned easily with a soft brush or vacuum.
<b>ASTM E1264 classification</b> Type XII, Form 2, Pattern E	<b>AC information</b> 170 for item #7003G. 190 for item #7013G.	<b>Metric sizes available</b> Contact sales for minimum quantities and lead times.
<b>ASTM E84 and CAN/ULC S102 surface-burning characteristics</b> Class A Flame spread: 25 or less Smoke developed: 50 or less	<b>Thermal resistance</b> R-3.3 (3/4" panels) R-4.4 (1" panels)	<b>Notes</b> 1. For details, see LEED report tool at usgdesignstudio.com or cgcdesignstudio.com. 2. LR values are shown as averages. 3. For details, see <i>USG 30-Year Limited System Warranty Commercial Applications</i> (SC2102) and <i>ClimaPlus™ Ceilings Certification of Performance</i> (SC2451). 4. Maximum 2'x2' with SQ edge panels.
<b>Weight</b> 0.29-0.36 lb./sq. ft.	<b>Maximum backloading</b> See <i>USG 30-Year Limited System Warranty Commercial Applications</i> (SC2102).	

### Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1839/rev. 11-16

© 2016 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by  
USG Interiors, LLC  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXL, DXT, DXW, PREMIER NUBBY, IT'S YOUR WORLD, BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

**USG** CGC