

# ULTIMA® Health Zone™

## ULTIMA® Health Zone™ High NRC

Square Lay-in  
fine texture




**TOTAL  
ACOUSTICS®**  
Sound Absorption (NRC)  
+ Sound Blocking (CAC)



**SUSTAIN®**  
High Performance  
Sustainable  
Ceiling Systems



CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



Ultima Health Zone Square Lay-in panels with Prelude XL 15/16" suspension system

Perfect for office, education, and healthcare spaces

Fine texture mineral fiber ceiling; combines exceptional acoustical performance, sustainability, and functionality attributes in one go anywhere ceiling panel that is especially durable and aesthetically pleasing for every healthy space.

### KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Meets or exceeds USDA/FSIS, FGI, HIPAA and ANSI S12.60 guidelines
- Anti-Bacterial/Mold/Mildew – BioBlock® Plus performance resists the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface
- Exceptional durability and cleanability – impact-, scratch-, and soil-resistant
- CleanAssure™ – safe for use with disinfectant cleaners
- Ultima® Health Zone™ panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Clean Room Performance up to ISO Class 5 (Class 100) using gasketed Clean Room™ suspension systems (Item 1935)

- Long-lasting water-repellency; washable and scrubbable
- Energy-saving, high light-reflective finish
- 30-Year Limited System Warranty against visible sag, mold, mildew, and bacterial growth
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

### TYPICAL APPLICATIONS


- Healthcare:
  - Patient rooms
  - Treatment rooms
  - Nurses' stations
  - Emergency rooms
  - Corridors
  - Lavatories and restrooms
  - Kitchen/food prep areas
- Education
- Office
- Clean Rooms (item 1935)

### COLOR



White (WH)

### DETAILS



1. Ultima® Health Zone™ Square Lay-in
2. Ultima® Health Zone™ High NRC Square Lay-in panels with Clean Room™ 15/16" suspension system

# ULTIMA® Health Zone™

## ULTIMA® Health Zone™ High NRC

Square Lay-in  
fine texture



RECYCLED CONTENT

UP TO  
76%

LEED V5

Ecomedes Data

### COMMON MATERIALS FRAMEWORK

Human Health	Declare Label HPD 3rd Party CDPH	Climate Health Ecosystem Health Circular Economy	EPD EPD ✓
OCCUPANT EXPERIENCE		Acoustics	✓

### VISUAL SELECTION

	armstrongceilings.com/suspdwgs	Susp. Dwg.	Dimensions Item No. (Inches)
ULTIMA® Health Zone™ High NRC		1, 6	1445 24 x 24 x 7/8" <input type="checkbox"/>
15/16" Square Lay-in			1448 24 x 48 x 7/8" <input type="checkbox"/>
ULTIMA Health Zone		1, 6	1935* 24 x 24 x 3/4" <input type="checkbox"/>
15/16" Square Lay-in			1938 24 x 48 x 3/4" <input type="checkbox"/>

1 Ctn Min  
**FASTSIZE**  
3 WEEKS  
order to ship

### PERFORMANCE SELECTION

	UL Classified Acoustics				Total Acoustics <sup>1</sup>				Articulation Class	Fire Performance	Light Reflect	Bio-Block+	Hum-Guard+ Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY				\$\$\$\$				
	NRC	+	CAC	=	NRC	CAC									Fog & Spray	Wipe	Water Repel	Wash	Scrub	Impact	Scratch	Soil	30-Yr Warranty
ULTIMA® Health Zone™ High NRC	0.80	•	35	*	BEST	(	170	*	Class A	0.86	*	+	*	*	*	*	*	*	*	*			
15/16" Square Lay-in	0.80	•	35	*	BEST	(	170	*	Class A	0.86	*	+	*	*	*	*	*	*	*	*			
ULTIMA Health Zone	0.70	•	38	*	BETTER	N/A	N/A	Class A	0.86	*	+	*	*	*	*	*	*	*	*	*			
15/16" Square Lay-in	0.70	•	38	*	BETTER	N/A	N/A	Class A	0.86	*	+	*	*	*	*	*	*	*	*	*			

### 3/4" or 7/8" Thick – 15/16" Square Lay-in

Made-to-Order Sizes	Width (short side)	Length (long side)
ULTIMA Health Zone	4" – 30"	12" – 72"


Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

\* Item provides Clean Room Performance up to ISO Class 5 (Class 100) using gasketed Clean Room™ suspension systems

### SUSPENSION SYSTEMS



### PHYSICAL DATA

**Material**  
Wet-formed mineral fiber with DuraBrite® acoustically transparent water-repellent membrane

**Surface Finish**  
DuraBrite with factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

**ASTM E1264 Classification**  
Type A, Form A2.2, Pattern E; Fire Class A

**Humidity/Sag Resistance**  
HumGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Bacterial/Mold/Mildew**  
Ceiling tiles with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface.

**VOC Emissions**  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustical Performance**  
CAC testing conducted using Prelude suspension system.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
R Factor – 2.9 (BTU units)  
R Factor – 0.445 (Watts units)

### Application Considerations

For Clean Room installations, use full-size panels. Testing for Clean Room 5 (Class 100) was completed with full-size 15/16" gasketed suspension system. For Clean Rooms that require field-cut perimeter panels, use Lay-in panels (1935) or Tegular panels (1937) with Lay-in field-cut panels at the perimeter.

### Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

**Weight: Square Feet/Carton**

1448, 1938 – 1.08 LBS/SF; 48 SF/CTN

1445 – 1.0 LBS/SF; 40 SF/CTN

1935 – 1.0 LBS/SF; 48 SF/CTN

**Minimum Order Quantity**  
1 carton